

DA 1260

Built-under rangehood



- Minimalist design – 598mm wide space-saving solution
- Powerful – 545m³/h on the booster setting
- Efficient filtration – 10-layer stainless-steel grease filter
- Safe and easy to clean – Miele CleanCover
- Suitable for every home – for extraction or recirculation

| | |
|---|-----------------|
| Construction type | |
| Built-in rangehood | • |
| Design | |
| Colour | Stainless steel |
| Operating modes | |
| Type of air guide | Convertible |
| User convenience | |
| Mechanical controls | • |
| Slide switch | • |
| Power levels (number without Booster level) | 3 |
| Booster level | • |
| Cleaning convenience | |
| CleanCover | • |
| Filter system | |
| Number of dishwasher safe stainless-steel grease filters (10-ply) | 2 |
| Lighting | |
| LED | • |
| Light intensity in Lx | 330 |
| Colour temperature in K | 3,000 |
| Fan | |
| Single-action fan | • |
| AC motor | • |
| Air throughput with max. duct diameter in extraction mode (not for external version) | |
| Air throughput in Level 1 (m ³ /h) | 275 |
| Air throughput in Level 2 (m ³ /h) | 315 |
| Air throughput in Level 3 (m ³ /h) | 355 |
| Air throughput in Booster level (m ³ /h) | 545 |
| Sound power in Level 1 (dB(A) re 1 pW) | 57 |
| Sound power in Level 2 (dB(A) re 1 pW) | 60 |
| Sound power in Level 3 (dB(A) re 1 pW) | 64 |
| Sound power in Booster level (dB(A) re 1 pW) | 74 |
| Sound pressure in Level 1 (dB(A) re 20 µPa) | 43 |
| Sound pressure in Level 2 (dB(A) re 20 µPa) | 47 |
| Sound pressure in Level 3 (dB(A) re 20 µPa) | 50 |
| Sound pressure in Booster level (dB(A) re 20 µPa) | 60 |

DA 1260

Built-under rangehood



| Air throughput in recirculation mode | |
|---|------|
| Air throughput in Level 1 (m ³ /h) | 165 |
| Air throughput in Level 2 (m ³ /h) | 180 |
| Air throughput in Level 3 (m ³ /h) | 195 |
| Air throughput in Booster level (m ³ /h) | 220 |
| Sound power in Level 1 (dB(A) re 1 pW) | 71 |
| Sound power in Level 2 (dB(A) re 1 pW) | 72 |
| Sound power in Level 3 (dB(A) re 1 pW) | 73 |
| Sound power in Booster level (dB(A) re 1 pW) | 75 |
| Sound pressure in Level 1 (dB(A) re 20 µPa) | 57 |
| Sound pressure in Level 2 (dB(A) re 20 µPa) | 58 |
| Sound pressure in Level 3 (dB(A) re 20 µPa) | 59 |
| Sound power in Booster level (dB(A) re 1 pW) | 62 |
| Technical data | |
| Canopy width in mm | 598 |
| Canopy height in mm | 125 |
| Canopy depth in mm | 500 |
| Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm | 650 |
| Net weight in kg | 11.2 |
| Length of supply lead in m | 1.5 |
| Standard plug fitted | • |
| Total rated load in kW | 0.24 |
| Voltage in V | 230 |
| Fuse rating in A | 10 |
| Number of phases | 1 |
| Installation notes | |
| Extraction ducting connection at top | • |
| Diameter of extraction ducting connection in mm | 150 |
| Fitting template | • |
| Standard accessories | |
| Non-return flap | • |
| Deflector for recirculation | • |
| Adapter to reduce ducting diameter from 150 mm to 125 mm Ø | • |