

DA 2390

Extractor unit



- Customised kitchen design – fully integrated in 884mm width
- Space-saving – suitable for narrow wall units over 30 cm deep
- Powerful – 600m³/h on the booster setting
- Efficient filtration – 10-layer stainless-steel grease filter
- Safe and easy to clean – Miele CleanCover

Construction type	
Integrated extractor	•
Design	
Colour	No colour
RAL colours available as customisation on request	•
Customisation possible on request	•
Operating modes	
Type of air guide	Convertible
User convenience	
Electronic controls	•
Light-touch controls	•
Power levels (number without Booster level)	3
Booster level	•
Cleaning convenience	
CleanCover	•
Filter system	
Number of dishwasher safe stainless-steel grease filters (10-ply)	2
Lighting	
LED	•
Light intensity in Lx	500
Colour temperature in K	3,000
Fan	
Dual-action fan	•
AC motor	•
Air throughput with max. duct diameter in extraction mode (not for external version)	
Air throughput in Level 1 (m ³ /h)	250
Air throughput in Level 2 (m ³ /h)	300
Air throughput in Level 3 (m ³ /h)	360
Air throughput in Booster level (m ³ /h)	600
Sound power in Level 1 (dB(A) re 1 pW)	47
Sound power in Level 2 (dB(A) re 1 pW)	48
Sound power in Level 3 (dB(A) re 1 pW)	52
Sound power in Booster level (dB(A) re 1 pW)	64
Sound pressure in Level 1 (dB(A) re 20 µPa)	31
Sound pressure in Level 2 (dB(A) re 20 µPa)	34
Sound pressure in Level 3 (dB(A) re 20 µPa)	38
Sound pressure in Booster level (dB(A) re 20 µPa)	50

DA 2390

Extractor unit



Air throughput in recirculation mode	
Air throughput in Level 1 (m ³ /h)	190
Air throughput in Level 2 (m ³ /h)	250
Air throughput in Level 3 (m ³ /h)	320
Air throughput in Booster level (m ³ /h)	500
Sound power in Level 1 (dB(A) re 1 pW)	54
Sound power in Level 2 (dB(A) re 1 pW)	60
Sound power in Level 3 (dB(A) re 1 pW)	64
Sound power in Booster level (dB(A) re 1 pW)	72
Sound pressure in Level 1 (dB(A) re 20 µPa)	39
Sound pressure in Level 2 (dB(A) re 20 µPa)	45
Sound pressure in Level 3 (dB(A) re 20 µPa)	49
Sound power in Booster level (dB(A) re 1 pW)	57
Safety	
Safety switch-off	•
Technical data	
Canopy width in mm	884
Canopy height in mm	63
Canopy depth in mm	297
Net weight in kg	13.0
Length of supply lead in m	1.5
Standard plug fitted	•
Total rated load in kW	0.23
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Installation notes	
Extraction ducting connection at top	•
Extraction connection at top and rear	•
Diameter of extraction ducting connection in mm	150
Standard accessories	
Non-return flap	•
Adapter to reduce ducting diameter from 150 mm to 125 mm Ø	•