

DA 2628

Extractor unit



- Customised kitchen design – fully integrated in 1,180mm width
- Unique user convenience – Con@ctivity
- Powerful – 890m<sup>3</sup>/h on the booster setting
- Energy-efficient and quiet – powerful ECO motor
- Elegant and efficient – edge extraction panels

<b>Construction type</b>	
Integrated extractor	•
<b>Design</b>	
Colour	Stainless steel
Edge extraction	•
<b>Operating modes</b>	
Type of air guide	air extraction
<b>User convenience</b>	
Electronic controls	•
Light-touch controls	•
Power levels (number without Booster level)	3
Booster level	•
Programmable Booster level switch-off	•
Run-on time 5 / 15 min.	•
Grease filter saturation indicator programmable	•
<b>Cleaning convenience</b>	
CleanCover	•
<b>Efficiency and sustainability</b>	
PowerManagement system	•
ECO package	•
<b>Appliance networking</b>	
Miele@home	•
WiFiConn@ct	•
MobileControl	•
Automatic function Con@ctivity 2.0 (Zigbee)	•
Automatic function Con@ctivity 3.0 (WiFi)	•
<b>Filter system</b>	
Number of dishwasher safe stainless-steel grease filters (10-ply)	4
<b>Lighting</b>	
LED	•
Light intensity in Lx	700
Colour temperature in K	3,500
Dimmer function	•
<b>Fan</b>	
Dual-action fan	•
ECO motor (DC motor)	•

DA 2628

Extractor unit



<b>Air throughput with max. duct diameter in extraction mode (not for external version)</b>	
Air throughput in Level 1 (m <sup>3</sup> /h)	315
Air throughput in Level 2 (m <sup>3</sup> /h)	475
Air throughput in Level 3 (m <sup>3</sup> /h)	640
Air throughput in Booster level (m <sup>3</sup> /h)	890
Sound power in Level 1 (dB(A) re 1 pW)	46
Sound power in Level 2 (dB(A) re 1 pW)	55
Sound power in Level 3 (dB(A) re 1 pW)	62
Sound power in Booster level (dB(A) re 1 pW)	70
Sound pressure in Level 1 (dB(A) re 20 µPa)	31
Sound pressure in Level 2 (dB(A) re 20 µPa)	41
Sound pressure in Level 3 (dB(A) re 20 µPa)	48
Sound pressure in Booster level (dB(A) re 20 µPa)	56
<b>Safety</b>	
Safety switch-off	•
<b>Technical data</b>	
Canopy width in mm	1,180
Canopy height in mm	64
Canopy depth in mm	293
Net weight in kg	15.0
Length of supply lead in m	1.5
Standard plug fitted	•
Total rated load in kW	0.24
Voltage in V	230
Fuse rating in A	10
Number of phases	1
<b>Installation notes</b>	
Extraction ducting connection at top	•
Extraction connection at top and rear	•
Diameter of extraction ducting connection in mm	150
<b>Standard accessories</b>	
Non-return flap	•
RF Con@ctivity 2.0 communication stick for KM	XKS 3000 Z