

DA 2668

Extractor unit



- Customised kitchen design – fully integrated in 580mm width
- Unique user convenience – Con@ctivity
- Powerful – 750m³/h on the booster setting
- Energy-efficient and quiet – powerful ECO motor
- Efficient filtration – 10-layer stainless-steel grease filter

Construction type	
Integrated extractor	•
Design	
Colour	Stainless steel
Edge extraction	•
Operating modes	
Type of air guide	Convertible
User convenience	
Electronic controls	•
Light-touch controls	•
Power levels (number without Booster level)	3
Booster level	•
Programmable Booster level switch-off	•
Run-on time 5 / 15 min.	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
Cleaning convenience	
CleanCover	•
Efficiency and sustainability	
PowerManagement system	•
ECO package	•
Appliance networking	
Miele@home	•
WiFiConn@ct	•
MobileControl	•
ShopConn@ct	•
Automatic function Con@ctivity 2.0 (Zigbee)	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Filter system	
Number of dishwasher safe stainless-steel grease filters (10-ply)	2
Lighting	
LED	•
Light intensity in Lx	700
Colour temperature in K	3,500
Dimmer function	•
Fan	
Dual-action fan	•
ECO motor (DC motor)	•

DA 2668

Extractor unit



Air throughput with max. duct diameter in extraction mode (not for external version)	
Air throughput in Level 1 (m ³ /h)	290
Air throughput in Level 2 (m ³ /h)	430
Air throughput in Level 3 (m ³ /h)	590
Air throughput in Booster level (m ³ /h)	750
Sound power in Level 1 (dB(A) re 1 pW)	46
Sound power in Level 2 (dB(A) re 1 pW)	56
Sound power in Level 3 (dB(A) re 1 pW)	65
Sound power in Booster level (dB(A) re 1 pW)	70
Sound pressure in Level 1 (dB(A) re 20 µPa)	32
Sound pressure in Level 2 (dB(A) re 20 µPa)	42
Sound pressure in Level 3 (dB(A) re 20 µPa)	50
Sound pressure in Booster level (dB(A) re 20 µPa)	55
Air throughput in recirculation mode	
Air throughput in Level 1 (m ³ /h)	220
Air throughput in Level 2 (m ³ /h)	350
Air throughput in Level 3 (m ³ /h)	410
Air throughput in Booster level (m ³ /h)	510
Sound power in Level 1 (dB(A) re 1 pW)	58
Sound power in Level 2 (dB(A) re 1 pW)	68
Sound power in Level 3 (dB(A) re 1 pW)	71
Sound power in Booster level (dB(A) re 1 pW)	74
Sound pressure in Level 1 (dB(A) re 20 µPa)	44
Sound pressure in Level 2 (dB(A) re 20 µPa)	54
Sound pressure in Level 3 (dB(A) re 20 µPa)	57
Sound power in Booster level (dB(A) re 1 pW)	60
Safety	
Safety switch-off	•
Technical data	
Canopy width in mm	580
Canopy height in mm	64
Canopy depth in mm	293
Net weight in kg	12.0
Length of supply lead in m	1.5
Standard plug fitted	•
Total rated load in kW	0.24
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Installation notes	
Extraction ducting connection at top	•
Extraction connection at top and rear	•
Diameter of extraction ducting connection in mm	150

DA 2668

Extractor unit



Standard accessories	
Non-return flap	•
RF Con@ctivity 2.0 communication stick for KM	XKS 3000 Z