

DA 6698 W Puristic Edition 6000

Wall mounted rangehood



- Family design – based on Miele built-in appliances
- Unique user convenience – Con@ctivity
- Powerful – 880m<sup>3</sup>/h on the booster setting
- Energy-efficient and quiet – powerful ECO motor
- Pleasantly quiet – Miele Silence package

<b>Construction type</b>	
Wall-mounted rangehood	•
<b>Design</b>	
Colour	Stainless steel
Customisation possible on request	•
Variable height available as customisation on request	•
<b>Operating modes</b>	
Type of air guide	Convertible
<b>User convenience</b>	
Electronic controls	•
Touch-on-glass controls	•
Power levels (number without Booster level)	3
Booster level	•
Programmable Booster level switch-off	•
Run-on time 5 / 15 min.	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
Silence package	•
<b>Cleaning convenience</b>	
CleanCover	•
<b>Efficiency and sustainability</b>	
PowerManagement system	•
ECO package	•
<b>Appliance networking</b>	
Miele@home	•
WiFiConn@ct	•
MobileControl	•
ShopConn@ct	•
Automatic function Con@ctivity 2.0 (Zigbee)	•
Automatic function Con@ctivity 3.0 (WiFi)	•
<b>Filter system</b>	
Number of dishwasher safe stainless-steel grease filters (10-ply)	3
<b>Lighting</b>	
LED	•
Light intensity in Lx	670
Colour temperature in K	3,500
Dimmer function	•
<b>Fan</b>	
Dual-action fan	•
ECO motor (DC motor)	•

DA 6698 W Puristic Edition 6000

Wall mounted rangehood



<b>Air throughput with max. duct diameter in extraction mode (not for external version)</b>	
Air throughput in Level 1 (m <sup>3</sup> /h)	320
Air throughput in Level 2 (m <sup>3</sup> /h)	480
Air throughput in Level 3 (m <sup>3</sup> /h)	640
Air throughput in Booster level (m <sup>3</sup> /h)	880
Sound power in Level 1 (dB(A) re 1 pW)	46
Sound power in Level 2 (dB(A) re 1 pW)	56
Sound power in Level 3 (dB(A) re 1 pW)	64
Sound power in Booster level (dB(A) re 1 pW)	72
Sound pressure in Level 1 (dB(A) re 20 µPa)	31
Sound pressure in Level 2 (dB(A) re 20 µPa)	41
Sound pressure in Level 3 (dB(A) re 20 µPa)	49
Sound pressure in Booster level (dB(A) re 20 µPa)	57
<b>Air throughput in recirculation mode</b>	
Air throughput in Level 1 (m <sup>3</sup> /h)	200
Air throughput in Level 2 (m <sup>3</sup> /h)	330
Air throughput in Level 3 (m <sup>3</sup> /h)	390
Air throughput in Booster level (m <sup>3</sup> /h)	460
Sound power in Level 1 (dB(A) re 1 pW)	55
Sound power in Level 2 (dB(A) re 1 pW)	65
Sound power in Level 3 (dB(A) re 1 pW)	68
Sound power in Booster level (dB(A) re 1 pW)	73
Sound pressure in Level 1 (dB(A) re 20 µPa)	40
Sound pressure in Level 2 (dB(A) re 20 µPa)	50
Sound pressure in Level 3 (dB(A) re 20 µPa)	53
Sound power in Booster level (dB(A) re 1 pW)	58
<b>Safety</b>	
Safety switch-off	•
Single pane tempered glass	•
<b>Technical data</b>	
Overall height for extraction mode and external mode cooker hoods in mm	710
Overall height for recirculation mode cooker hoods in mm	840
Canopy width in mm	898
Canopy height in mm	85
Canopy depth in mm	500
Net weight in kg	26.0
Length of supply lead in m	1.5
Standard plug fitted	•
Total rated load in kW	0.24
Voltage in V	230
Fuse rating in A	10
Number of phases	1

DA 6698 W Puristic Edition 6000

Wall mounted rangehood



<b>Installation notes</b>	
Extraction ducting connection at top	•
Extraction connection at top and rear	•
Diameter of extraction ducting connection in mm	150
Telescopic chimney	•
Telescopic wall bracket	•
<b>Standard accessories</b>	
Non-return flap	•
Adapter to reduce ducting diameter from 150 mm to 125 mm Ø	•
RF Con@ctivity 2.0 communication stick for KM	XKS 3000 Z