

KM 6520 FR

Electric cooktop with onset controls with 4 cooking zones for maximum convenience.



- Easy operation EasySelectAttractive design 574mm wide with all-round frame
- Particularly versatile 4 cooking zones incl. 1 Vario zone
- Convenient Auto heat-up for every cooking zone
- Safe three level residual heat indicator for every cooking zone

n convenience.	
Heating type	
Heating type	Electrical
Construction type	
Independent of cooker	•
Design	
Elegant glass ceramic surface	
Ceramic surface colour	Black
Stainless-steel frame	<u> </u>
Surface-mounted installation	•
Cooking zone details	4
Number of cooking zones Cooking zone	4
Position	front left
Туре	Single-circuit ring
Size in mm	Ø 180
Max. rating in W	1800
Position	rear left
Type	Single-circuit ring
Size in mm	Ø 160
Max. rating in W	1500
Position	rear right
Type	Dual-circuit ring
Size in mm	120/210 mm
Max. rating in W	750/2200
Position	front right
Type	Single-circuit ring
Size in mm	Ø 145
Max. rating in W	1200
User convenience	
Display colour	Yellow
Stop & Go function	•
Recall function	•
Minute minder	•
Safety switch-off	•
Auto heat-up	•
Individual setting options (e.g. buzzers)	•
Efficiency and sustainability	
Residual heat utilisation	•
Cleaning convenience	
Easy to clean ceramic glass	•



KM 6520 FR Electric cooktop with onset controls with 4 cooking zones for maximum convenience.




Safety	
Safety switch-off	•
Lock function	•
System lock	•
Overheating protection	•
Residual heat indicator	•
Technical data	
Dimensions in mm (width)	574
Dimensions in mm (height)	43
Casing height incl. connection box in mm	43
Dimensions in mm (depth)	504
Cutout dimensions in mm (width) with surface-mounted installation	560
Cutout dimensions in mm (depth) with surface-mounted installation	490
Weight in kg	8
Total rated load in kW	6.7
Voltage in V	230
Connection cable length in m	1.4
Standard accessories	
Razor-blade scraper	•
Mains cable	•



KM 6520 FR

Electric cooktop with onset controls with 4 cooking zones for maximum convenience.





KM 6520 FR, KM 6538 FR (Installation drawign)

- 1) Front 2) Mains Connection box. Built-in height 43 mm, mains connection cable L = 1440 mm