

#### WWD164 WCS 9kg

## W1 front loader washing machine

Combining style with Miele quality and reliability, enjoy gentle care for your garments with the Miele



- Gentle XL laundry care with the 9 kg honeycomb drum
- Ironing made simple thanks to preironing with steam
- Miele@home clever networking opens up new possibilities\*
  MobileControl ensure complete flexibility using the Miele App
- Perfect supplement for specific applications CapDosing
- Smart laundry care with WiFiConn@ct

Construction type	
Suitable for stacking	•
Side-by-side	•
Built-in	
Door hinge	right
Model	
Product brand	W1 White Edition
Front-loader	ask.
Spinning	
Max. spin speed	1400
Rinse hold	1722
Without spin function	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Door design	Obsidian Black with white ring
Rotary selector colour	Lotus White
Control panel version	5° inclined
Control type	Rotary selector
Display	DirectSensor yellow, 7 segment
Cleaning performance	
CapDosing portioned dispensing	•
Gentle laundry care	
Honeycomb drum	<u>, *</u>
Load in kg	9
User convenience	
Networking with Miele@home	
Delay start up to 24 hours	
Time left display	•
AutoClean detergent drawer	•
AddLoad	•
Efficiency and sustainability	
Low temperature wash "Cold" and "20 °C"	
Automatic load control	
Flow meter	•
Foam sensing	•
ProfiEco motor	•

# Míele

### WWD164 WCS 9kg

### W1 front loader washing machine

Combining style with Miele quality and reliability, enjoy gentle care for your garments with the Miele



Wash programmes	
Cottons (coloureds)	•
Minimum iron	•
Delicates	•
Shirts	•
Woollens (hand-washable)	•
Express 20	•
Dark garments/Denim	•
Proofing	•
Drain/Spin	•
ECO 40-60	•
Washing extras	
Short	•
Pre-wash	•
Water plus	•
Additional rinse cycle	•
Pre-ironing with steam	•
Buzzer	•
Quality	
Counterweights made of cast iron	•
Safety	
Water protection system	Watercontrol-System
PIN code	•
Optical interface	•
Technical data	500
Dimensions in mm (width)	596
Dimensions in mm (height)	850
Dimensions in mm (depth)	643
Appliance depth in mm with opened door	1077
Weight in kg	91
Total rated load in kW	2.3
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50
Length of supply lead in m	2