

DAS 4920
Slimline rangehood
with EasySwitch controls for convenient operation



- Classic design – stainless steel panel, 90 cm wide
- Unique user convenience – Con@ctivity
- LED strip for uniform lighting
- Efficient filtration – 10-layer stainless-steel grease filter
- Recirculation mode – Active AirClean or Longlife AirClean filter

EAN: 4002516805861 / Material number: 12569030

Construction type	
Slideout rangehood	•
Operating modes	
Type of air guide	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151
Active charcoal filter (order separately)	DKFS 31-P, DKFS 31-R
Design	
Colour	Matte Black
User convenience	
Miele@home	•
Automatic function Con@ctivity	•
Electronic controls	•
Touch-on-glass controls	•
Programmable Booster level switch-off	•
Run-on time 5/15 min.	•
Grease filter saturation indicator	•
Grease filter saturation indicator programmable	•
Active charcoal filter saturation indicator programmable	•
Easy-to-clean canopy interior – CleanCover	•
Efficiency and sustainability	
Fan power (m ³ /h)	1145
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	1
Lighting	
LED	•
Number x W	1 x 3 W
Light intensity in Lx	300 lx
Colour temperature in K	3500 Kelvin
Dimmer function	•
Blower	
Dual-action fan	•
AC motor	•
Extraction	
Air throughput in Level 1 (m ³ /h) according to EN 61591	345
Air throughput in Level 2 (m ³ /h) according to EN 61591	500
Air throughput in Level 3 (m ³ /h) according to EN 61591	655
Air throughput in Booster level (m ³ /h) according to EN 61591	925
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	50.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	59.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	65.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	73.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	36.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	45.0



DAS 4920
Slimline rangehood
with EasySwitch controls for convenient operation



EAN: 4002516805861 / Material number: 12569030

Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	51.0
Sound pressure in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	59.0
Recirculation	
Air throughput in Level 1 (m ³ /h) according to EN 61591	345
Air throughput in Level 2 (m ³ /h) according to EN 61591	495
Air throughput in Level 3 (m ³ /h) according to EN 61591	655
Air throughput with Booster setting 1 (m ³ /h) according to EN 61591	865
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	58.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	68.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	74.0
Sound power with Booster setting 1 (dB(A) re 1 pW) acc. to EN 60704-3	81.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	44.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	54.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	60.0
Sound pressure with Booster setting 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	67.0
Safety	
Safety switch-off	•
Technical data	
Canopy width in mm	896
Canopy height in mm	36
Canopy depth in mm	273
Net weight in kg	16.0
Length of supply lead in m	1.8
Standard plug fitted	•
Total rated load in kW	0.29
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Frequency in Hz	50
Installation notes	
Extraction ducting connection at top	•
Diameter of exhaust duct in mm	150
Accessories supplied	
Non-return flap	•

DAS 4920 Installation diagrams



DAS2920, DAS2920EXTA, DAS2922Living, DAS4920,
Installation drawings

1) The front section of the wall unit must be fitted with a base panel to secure the cooker hood. If the appliance is fitted further back, e.g. to accommodate a front panel, then the shelf depth should be deeper accordingly. , 2) If a partition wall is to be provided in the unit, it must be removable., 3) Extraction, recirculation with conversion kit DUU 150., 4) Mounting is also possible in a 600 mm wide cabinet., * In this installation situation, the deflector plate is flush with the front edge of the housing unit carcass. , If you wish to position the cooker hood further forward or further back (e.g. because it has a front panel), dimensions have to be adapted accordingly., , Extraction: the height of the wall unit and the cut-out dimensions must take into account any accessories fitted, e.g. silencer, recirculation hood conversion kit).