

N 90, Built-in oven with added steam function, Stainless steel  
B58VT68H0B



COOKING PASSION SINCE 1877



Built-in oven with VarioSteam® and SLIDE&HIDE® - fuller flavour and unrestricted access to the oven interior.

- ✓ Slide&Hide® - the door disappears underneath the oven for unrestricted access and the handle rotates for easy handling
- ✓ CircoTherm® - our smart hot-air solution for simultaneous baking and roasting on up to four levels
- ✓ Vario Steam - steam assistance that cooks food moist on the inside and crisp on the outside
- ✓ The duo for perfect cleaning: Pyrolysis after heavy use - the oven interior cleans itself. EasyClean® - the environment-saving option for fast oven cleaning.
- ✓ Multipoint Meatprobe - the thermometer helps the oven regulate the temperature and automatically adjust the cooking time

Features

Technical Data

Color / Material Front : Stainless steel  
 Built-in / Free-standing : Built-in  
 Integrated Cleaning system : Hydrolytic, Pyrolytic  
 Required niche size for installation (HxWxD) : 585-595 x 560-568 x 550  
 Dimensions of the product (mm) : 595 x 596 x 548  
 Dimensions of the packed product (HxWxD) (mm) : 670 x 690 x 660  
 Control Panel Material : Stainless steel  
 Door Material : Glass  
 Net weight (kg) : 45.100  
 Usable volume of cavity (l) : 71  
 Cooking method : Bottom heat, Bread Baking Setting, Conventional heat, Defrost, Full width grill, Half width grill, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza setting, pre-heating, warming  
 Oven control : electronic  
 Number of interior lights : 3  
 Approval certificates : CE, VDE  
 Length electrical supply cord (cm) : 120  
 EAN code : 4242004236092  
 Number of cavities (2010/30/EC) : 1  
 Energy efficiency class (2010/30/EC) : A  
 Energy consumption per cycle conventional (2010/30/EC) : 0.90  
 Energy consumption per cycle forced air convection (2010/30/EC) : 0.74  
 Energy efficiency index (2010/30/EC) : 87.1  
 Connection Rating (W) : 3450  
 Current (A) : 16  
 Voltage (V) : 220-240  
 Frequency (Hz) : 50; 60  
 Plug type : no plug



Optional accessories

- |           |   |
|-----------|---|
| Z11SZ00X0 | SeamlessCombination mounting kit        |
| Z11SZ80X0 | SeamlessCombination 60 + 29cm           |
| Z11SZ90X0 | SeamlessCombination 60 + 45cm           |
| Z11TC10X0 | ComfortFlex Rail (1 level)              |
| Z12CB10A0 | Baking tray, anthracite enamelled       |
| Z12CM10A0 | Moussaka pan, anthracite enamelled      |
| Z12CU10A0 | Multipurpose pan, anthracite enamelled  |
| Z12TF36X0 | 3 level telescopic rails, full ext,pyro |
| Z1913X0   | Baking Stone                            |



4 242004 236092

*N 90, Built-in oven with added steam function,  
Stainless steel  
B58VT68H0B*

## Features

### Heating Functions

- Additional heating methods with steam: Reheating, Dough Proving
- Cavity volume: 71 net usable litres

### Design

- Anthracite enamel cavity with 4 shelf positions

### Cleaning

- Pyrolytic self cleaning
- EasyClean® Cleaning aid programm

### Convenience

- 5.7" TFT colour and graphics Display with FullTouch control
- Additional functions: Descaling program Steam cooking function (system steamer accessory required) drying function
- Slide&Hide® door, SoftOpen
- Bake and Roast assist, Automatic programs
- Number of automatic programmes: 14 PC
- MultiPoint MeatProbe
- Electronic clock with start / stop function
- Rapid heating-up: automatic
- NeffLight®, LED lighting
- Large 1 litre water tank
- Water tank empty indicator
- Location of the steam generator is outside of the cavity
- Cooling fan
- Stainless-steel fan

### Hook-in racks / rails

### Accessories

- 1 x combination grid, 2 x universal pan

### Safety and Environment

- Individual adjustable child lock Safety switch off Residual heat indicator Start button Door contact switch

### Technical Info

- Length of mains cable: 120 cm
- Total connected load electric: 3.45 KW
- Appliance dimensions (HxWxD): 595 mm x 596 mm x 548 mm
- Installation dimensions (HxWxD): 585 mm - 595 mm x 560 mm - 568 mm x 550 mm
- Please reference the built-in dimensions provided in the installation drawing