N 50, Built-in oven, Stainless steel B6ACH7AN0A







Optional accessories

Z11TF36X0	3 level telescopic rails, full ext
Z1913X0	Baking Stone

Built-in oven with Hide[®] - the fully retracting oven door

- $\sqrt{\rm CircoTherm^{\odot}}$ Neff's outstanding hot-air system for simultaneous baking and roasting on up to 3 levels.
- $\sqrt{}\,$ Hide^® the fully retracting oven door.
- $\checkmark\,$ The duo for perfect cleaning: Pyrolysis after heavy use the oven interior cleans itself.
- $\checkmark\,$ EasyClean® the environment-saving option for fast oven cleaning.
- $\sqrt{}$ Modern LED lighting for bright, even illumination.

Features

 $\sqrt{}$

Technical Data

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Integrated Cleaning system : Hydrolytic, Pyrolytic Required niche size for installation (HxWxD) : 585-595 x 560-568 x 550 Dimensions of the product (mm) : $595 \times 594 \times 548$ Dimensions of the packed product (HxWxD) (mm) : 660 x 690 x 650 Control Panel Material : Glass Door Material : Glass Net weight (kg) : 38.124 Usable volume of cavity (I) : 71 Cooking method : Bottom heat, Bread Baking Setting, Conventional heat, Full width grill, Hot Air, Hot air grilling, Pizza setting First cavity material : Other Oven control : electronic Number of interior lights : 1 Approval certificates : CE, VDE Length electrical supply cord (cm) : 120 EAN code : 4242004237860 Number of cavities (2010/30/EC) : 1 Energy efficiency class (2010/30/EC) : A Energy consumption per cycle conventional (2010/30/EC) : 1.04 Energy consumption per cycle forced air convection (2010/30/EC) : 0.81 Energy efficiency index (2010/30/EC) : 95.3 Connection Rating (W) : 3600 Current (A) : 16 Voltage (V) : 220-240 Frequency (Hz) : 60; 50 Plug type : no plug



N 50, Built-in oven, Stainless steel B6ACH7AN0A

Features

Heating Functions

- Oven with 8 heating methods:
- CircoTherm[®] Top/bottom heating Circo-roasting Full surface grill CircoTherm[®] Intensive Bread Baking Bottom heating Hotair gentle
- Temperature range 30 °C 275 °C
- Cavity volume: 71 net usable litres

Design

- Rotary Control, Retractable control knobs
- Enamel grey with 4 shelf positions

Cleaning

- Pyrolytic self cleaning
- EasyClean® Cleaning aid programm
- Full glass inner door safer touch door

Convenience

- White LCD display
- Temperature proposal automatic start Optical temperature control Actual temperature display Sabbath setting
- Hide door
- Electronic clock
- Rapid heating-up
- Halogen lighting
- Cooling fan
- Bar handle

Hook-in racks / rails

• Large capacity oven with shelf supports, Telescopic shelf rails available as optional accessory

Accessories

• 1 x combination grid, 1 x universal pan

Safety and Environment

- Automatic door lock during pyrolysis Individual adjustable child lock Safety switch off Residual heat indicator
- Quadruple glazed CoolTouch door
- Maximum door temperature 30° C

Technical Info

- Length of mains cable: 120 cm
- Nominal voltage: 220 240 V
- Total connected load electric: 3.6 KW
- Appliance dimensions (HxWxD): 595 mm x 594 mm x 548 mm
- \bullet Installation dimensions (HxWxD): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please reference the built-in dimensions provided in the installation drawing