

**Serie | 6, Wall-mounted cooker hood,
90 cm, Stainless steel
DWB97LM50A**



The wall-mounted rangehood: a functional design element in the kitchen.

- **Extraction rate:** at 697 m³/h, it quickly ensures optimal kitchen air quality.
- **Especially quiet:** high performance at just 55 dB.
- **LED lighting:** for perfect, energy-efficient illumination of the cooktop.
- **Intensive speed setting with reset:** automatically resets the hood to regular speed setting after 6 min.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	Australia Standards, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	582-908/582-1018
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	18.913
Type of control :	Electronic
Maximum output air extraction (m ³ /h) :	431
Boost position output recirculating (m ³ /h) :	372
Maximum output recirculating air (m ³ /h) :	319
Boost position air extraction (m ³ /h) :	697
Number of lights :	3
Noise level (dB) :	55
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242005107728
Connection Rating (W) :	145
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	AU plug
Installation typology :	Wall-mounted

Optional accessories

DHZ5345 : Recirculating kit

DSZ6240 : CleanAir Recirculation Kit



4 242005 107728

Serie | 6, Wall-mounted cooker hood, 90 cm, Stainless steel DWB97LM50A

The wall-mounted rangehood: a functional design element in the kitchen.

Design & Innovation

- Box design
- Appliance colour: Stainless steel
- Power and Mode of Operation
- 3 power settings plus intensive setting
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 431 m³/h
Intensive 697 m³/h
- Extraction rate in recirculation mode:
Max. normal use: 319 m³/h
- Ducted and recirculated-air operation
- Electronic controls with white LED display
- TouchControl
- EcoSilence BLDC brushless motor
- Noise min./max. Normal Level: 45/55 dB
Noise max. Intensive setting: 66 dB
- Noise level in recirculation mode:
Max. normal use: 70 dB(A) re 1 pW (57 dB(A) re 20 μ Pa sound pressure)
- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)
- Average Energy Consumption: 33.1 kWh/year
- Power rating: 145 W

Comfort & Convenience

- with one-way flap: prevents outside air from entering your kitchen
- Dishwasher safe metal grease filters
- 3 x 1.5 Watt LED Lights
- Intensive operation automatic revert - 6min
- Additional sound insulation mats for optimised sound absorption

Technical Information

- Appliance width: 898 mm
- Dimensions exhaust air (HxWxD): 628-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 898 x 500 mm
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Electrical cable length 1.3 m

Serie | 6, Wall-mounted cooker hood, 90 cm, Stainless steel DWB97LM50A

