

ERI842DSD

86cm integrated rangehood in dark stainless steel with Hob2Hood technology, maximum airflow of 680 m3/hr and efficient perimeter extraction.

RRP AUS \$1,109.00





# **Product Details**

FEATURES			
Hob2Hood technology	Max airflow of 680m3/h	Operation noise as low as 51dB(A)	Multi-layer filters
Dishwasher safe filters	LED lighting	3 speed fan + Boost Function	
BENEFITS			
The hands free hood While you concentrate on the flavours, the innovative Hob2Hood feature will take care of keeping your kitchen fresh. The rangehood automatically turns on as soon as you start cooking, and intuitively adjusts the fan speed with your cooking.		Maximise your airflow Remove odours and vapours airflow rate of 680m3/h	quickly and efficiently with a high
Keep the noise down With noise levels as low as 51dB(A), keep the conversation going smoothly when entertaining guests.		Best of both worlds Perimeter extraction gives you whisks away odours efficientl	



# **Specifications**

## PRODUCT PROFILE

Domestic warranty details (yrs)	2
Type of Rangehood	integrated
Nominal width	900
Finish of Rangehood	Dark stainless steel

### MOTOR/FAN

**CONTROLS** 

Number of fans	2
Number of fans speeds	3
Type of motor	tangential
Perimeter extraction	Yes
Maximum airflow M3/Hr	680
Noise level dB high	66
Noise level dB low	51

## DIMENSIONS

Total product height (mm)	330
Total product width (mm)	860
Total product depth (mm)	300
Diameter of ducting (mm)	150
Minimum installation height from cooking surface Gas (mm)	650

Control panel	electronic push button
LED speed display	No
Removal front fascia	No
Hob2Hood function	Yes



### DIMENSIONS

Minimum installation height 600 from cooking surface Electric (mm)

### FILTERS

Number of filters	2
Type of filter	multilayer aluminum micromesh filters
Dishwasher safe	Yes

### LIGHTS

Number of lights	2
Wattage of light	2
Type of light	LED

# DUCTING / RECIRCULATION

Ducting	optional accessory
Top or rear duct hole	top
Recirculation option	Yes
Ducting diameter (mm)	150

## SHIPPING

Shipping Volume (m3)	0.154
Shipping Weight (Kg)	11
Pack Dimensions Height (mm)	430
Pack Dimension Width (mm)	365
Pack Dimension Depth (mm)	980



# STUFFING QUANTITIES

20ft	188
40ft	388
40ft HC	388



# **Terms and Conditions**

#### IMPORTANT

This is a guide of product dimensions only. For complete installation instructions, refer to the manual provided with product.

#### **PRODUCT INFORMATION**

The descriptors and illustrations in this publication apply to the specific products and models described as at the date of issue. Under our policy of continuous productdevelopment, product specifications may change without notice. Prospective purchasers should therefore check with their retailer to ensure this publication correctly describes theproducts that are being offered for sale. All information supplied is to be used for general reference purposes only and is on the understanding that Electrolux Home Products PtyLtd (Australia) and Electrolux (NZ) Ltd (New Zealand) will not be liable for any loss, liability or damage of whatever kind arising as a result of reliance on such information. Colours ofproducts illustrated are as close as printing limitations allow. Electrolux will at all times comply with its obligations pursuant to law including Trade Practices (Australian Consumer Law) Act and Regulations.

#### WARRANTY

This warranty only applies to Appliances purchased and used in Australia or New Zealand and used in normal domestic applications and is in addition to (and does not exclude, restrict, or modify in any way) any non-excludable statutory warranties in Australia or New Zealand. All warranties are subject to the conditions set out in the warranty card accompanying the product when purchased.

#### ELECTROLUX HOME PRODUCTS AUSTRALIA

telephone: 1300 363 640 fax: 1800 350 067 email: customercare@electrolux.com.au web: www.electrolux.com.au

### ELECTROLUX HOME PRODUCTS NEW ZEALAND telephone: 09 573 2230 fax: 09 573 2221 email: customercare@electrolux.co.nz web: www.electrolux.co.nz