

# Series 6, Gas cooktop, 75 cm, Tempered Glass, Black PPQ7A6B21A





HEZ211310 Simmer cap HEZ298105 Simmer plate

# The tempered-glass gas cooktop with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- FlameSelect: adjust the gas flame precisely using nine defined levels.
- Wok burner: powerful cooking at up to 15 Mj/h.
- Surface colour: elegant black tempered-glass design.
- Sword knobs: for an ergonomic control.

Product name/family:gas hob w integrated controls
Built-in / Free-standing: Built-in
Energy input:Gas
Total number of positions that can be used at the same time: 5
Type of control setting devices:Sword knobs
Min. required niche size for installation (HxWxD):45 x 560-562 x
480-492 mm
Width of the appliance:752 mm
Dimensions (HxWxD): 58 x 752 x 520 mm
Dimensions of the packed product (HxWxD): 145 x 793 x 597 mm
Net weight:
Gross weight:
Residual heat indicator: without
Location of control panel: Front
Basic surface material: Tempered Glass
Color of surface:Black
Color of frame:Black
Length electrical supply cord:
EAN code:
Gas connection rating:
Fuse protection:
Voltage:
Frequency: 50; 60 Hz





# Series 6, Gas cooktop, 75 cm, Tempered Glass, Black PPQ7A6B21A

The tempered-glass gas cooktop with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

### Design

- Black, Tempered Glass surface
- Single pan supports, cast iron

### Usage convenience

- FlameSelect (9 steps): precisely adjust the flame in nine defined and consistent levels.
- sword knobs: easily access knobs in front with strong grip for effortless turning.
- One-hand electronic ignition via controls: just push and turn the knob to ignite the flame.

## **Burners and power**

- 5 Gas burners
- Left front: Economy burner up to 4 Mj/h (depending on gas type)
- Left rear: Standard burner up to 6.5 Mj/h (depending on gas type)
- Center front: Dual flame wok burner up to 15 Mj/h (depending on gas type)
- Right rear: High-speed burner up to 11 Mj/h (depending on gas type)
- Right front: Standard burner up to 6.85 Mj/h (depending on gas type)

### Safety

- Flame failure device fitted to each individual burner: prevents unwanted gas flow when flame goes out.

### Installation (gas types & measurements)

- Dimensions of the product (HxWxD mm):  $58 \times 752 \times 520$
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm

### Accessories

- 1 x Wok attachment ring, cross support for espresso included
- Nozzle set for Liquid gas nozzles (28-30/37mbar) included.
- Power cord 1 m with plug.