

# Series 6, Gas cooktop, 90 cm, Tempered Glass, Black PPS9A6B91A





HEZ298105 Simmer plate

# The tempered-glass gas cooktop with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

- FlameSelect: adjust the gas flame precisely using nine defined levels.
- Wok burner: powerful cooking at up to 15 Mj/h.
- Semi-continuous cast-iron pan support: for high stability and easy cleaning.
- Sword knobs: for an ergonomic control.
- Surface colour: elegant black tempered-glass design.

Product name/family: .....gas hob w integrated controls Built-in / Free-standing: ...... Built-in Energy input: ......Gas Total number of positions that can be used at the same time: ....... 5 Type of control setting devices: ......Sword knobs Min. required niche size for installation (HxWxD): .....45 x 850-852 x 490-502 mm Width of the appliance: ......915 mm Dimensions of the packed product (HxWxD): ... 165 x 1116 x 659 mm Residual heat indicator: ......without Location of control panel: ..... Front Basic surface material: ...... Tempered Glass Color of surface: ......Black Length electrical supply cord: ......150.0 cm Gas connection rating: ...... 11500 W 





# Series 6, Gas cooktop, 90 cm, Tempered Glass, Black PPS9A6B91A

The tempered-glass gas cooktop with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

#### Design

- Black, Tempered Glass surface
- Single pan supports, cast iron

#### Usage convenience

- FlameSelect (9 steps): precisely adjust the flame in nine defined and consistent levels.
- sword knobs: easily access knobs in front with strong grip for effortless turning.
- One-hand electronic ignition via controls: just push and turn the knob to ignite the flame.

## **Burners and power**

- 5 Gas burners
- Left: Wok burner up to 15 Mj/h (depending on gas type)
- Center front: Economy burner up to 3.8 Mj/h (depending on gas type)
- Center rear: Standard burner up to 6.85 Mj/h (depending on gas type)  $\,$
- Right rear: High-speed burner up to 11 Mj/h (depending on gas type)
- Right front: Standard burner up to 6.85 Mj/h (depending on gas type)

# Safety

- Flame failure device fitted to each individual burner: prevents unwanted gas flow when flame goes out.

# Installation (gas types & measurements)

- Dimensions of the product (HxWxD mm): 58 x 915 x 520
- Required niche size for installation (HxWxD mm) :  $45 \times 850 \times (490 502)$
- Min. worktop thickness: 30 mm

## **Accessories**

- 1 x Wok attachment ring, cross support for espresso included
- Nozzle set for Liquid gas nozzles (28-30/37mbar) included.
- Power cord 1.5 m with plug.