



Quality, Design and Innovation



LIEBHERR



2.4" Touchscreen Display: Located behind the appliance door, this high-resolution and high-contrast 2.4" touchscreen display can be read from any angle. Stored menu options are Intuitive and easy-to-operate.



BioFresh: When stored at Biofresh's precisely maintained temperature of 0°C and correct humidity level, nutrients in your food are retained. Our BioFresh drawers fully extend on telescopic rails and feature a self-closing mechanism.



PowerCooling: A high-performance system that allows freshly stored items to be chilled rapidly while maintaining an even temperature throughout the interior. In this energy-efficient BluPerformance range, the fan switches off when the appliance door is opened, saving valuable energy.

When looking for optimum fresh food storage, look no further than the **SKBbs 4350** BlackSteel fridge with BioFresh. From our BluPerformance range, this appliance combines perfect cooling performance for long-lasting freshness, ample storage space, and a classic design.

All its three BioFresh drawers run on telescopic rails and provide optimal storage conditions for your groceries at a temperature of just above 0°C in combination with ideal humidity. The SuperCool function allows food to be cooled quickly. And for storage of small condiments, pastes or medicines, VarioSafe makes it possible.

os 4300	1 4050
Fresh System Telescopie Ste	Bbs 4350 Bio Fresh Soft Soft Soft System Telescopic Stee

Energy consumption (kWh/yr) I Star rating	194 4.0
Compressors	1
Total capacity litres (L) - Gross I Net	411 367
Refrigerator gross (L) I Refrigerator net (L)	250 234
BioFresh gross (L) I BioFresh net (L)	161 133
Control system and display Child proof	2.4"Touch display I Yes
PremiumPlus lighting	Yes
Sabbath mode	Yes
SoftSystem hinge - assists closure	Yes
Door open alarm	Yes
BioFresh drawers on telescopic rails	3
SuperCool VarioSafe	Yes I Yes
Integrated bottle shelf	Yes
Stainless steel door with SmartSteel	Yes
Stainless steel walls with SmartSteel	Yes
Default hinge	Right
Voltage (V) Rated Current (A)	220 - 240 1.2
Made in	Germany

